

C-AR-DD-3L Series

LED Dusk to Dawn

Replaces up to 70W MH



A CUSTOMER FAVORITE, NOW IN LOWER LUMEN OPTIONS

This product brings a breadth of versatility to the Dusk to Dawn family with a lower lumen output and surge protection. All while maintaining the same great benefits of the family line!



PRODUCT SPECIFICATIONS

OVERVIEW

- Initial Delivered Lumens: 2,800
- CRI: ≥ 70
- CCT: Cool White 5000K
- Mounting: Mounts directly to wall surface or to pole with mounting arm (accessory sold separately)
- Input Power: 23 Watts
- Dimmable: No
- Operating Minimum: -30°C (-22°F)
- Lifespan: Estimated >50,000 Hours
- Power Factor: > 0.9
- Total Harmonic Distortion: < 20%
- Limited Warranty: 5 Years*
- Replaces 70W MH

EFFICIENT	ADVANCED TECHNOLOGY	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none">• Included photocell for dusk to dawn operation• Solid state LED technology	<ul style="list-style-type: none">• 6kVA surge protection guards against electrical surges & increases reliability• Wall mount lag bolt pattern aligns with most traditional bolt patterns for easy installation included	<ul style="list-style-type: none">• General Area Illumination• Entryways & Pathways• Yards & Loading Docks	<ul style="list-style-type: none">• Universal (120V through 277V Operation)


ORDERING INFORMATION

Example: C-AR-DD-3L-50K-GR

C-AR-DD	3L	50K	GR
PRODUCT	LUMEN PACKAGE	CCT	COLOR
C-AR-DD	3L 2,800 Lumens 23W	50K Cool White (5000K)	GR Gray

CERTIFICATIONS:

C-AR-DD-3L Series



SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
12" L x 7-1/2" W x 6-3/4" H	2.2 lbs.	10 to 15 feet	---

FIXTURE SPECIFICATIONS

HOUSING	Durable, die-cast aluminum heat sink & housing Gray polyester powder-coat finish Twist-lock photocell included
LENS ASSEMBLY	UV-stabilized acrylic prismatic refractor White polycarbonate reflector
MOUNTING	Mounts directly to wall surface or to pole with mounting arm (accessory sold separately)

ELECTRICAL PERFORMANCE


OPERATING MINIMUM	LIFESPAN L ₇₀ AT 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION	DIMMABLE
-30°C (-22°F)	Estimated >50,000 Hours	> 0.9	< 20%	No
INPUT VOLTAGE	120V	208V	240V	277V
CURRENT DRAW (Amps)	0.19A	0.11A	0.096A	0.083A

WARRANTY AND CERTIFICATIONS

WARRANTY	UL LISTED
5 Year Limited*	Wet Locations

C-AR-DD-3L Series

ACCESSORIES

	MOUNTING ARM KIT
	SKU: C-ACC-A-SMDDPOLE-GR (120V) Use: For pole mounting

© 2017 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Patent www.cree.com/patents. The CREE LEDs logo, C-LITE™ and the C-LITE logo are trademarks of Cree, Inc. The UL logo is a registered trademark of UL LLC.

US: c-lite.com T (800) 236-6800 F (262) 504-5415

Canada: www.cree.com/canada T (800) 473-1234 F (800) 890-7507

Rev. Date: V1 05/24/2018

For informational purposes only. Content is subject to change. *See lighting.cree.com/warranty for details

C-LITE
LED LIGHTING BY CREE