

C-STRIP-B-SCCT Series

Linear LED Strip Light with Field Selectable CCT and Wattage

Replaces up to 2-lamp 54W T5HO



THREE FIXTURES; ONE LINEAR STRIP

Select your savings with our cULus Listed LED Linear Strip Lights in 2-, 4-, and 8-foot lengths. Achieve your desired performance with field switchable CCTs from 3000K, 4000K, or 5000K; and select your wattage, with up to 3 lumen outputs. Each comes with a 5-year limited warranty, and a variety of available accessories.

PRODUCT SPECIFICATIONS

OVERVIEW

- Max. Delivered Lumens: 2630 (**S26L**); 5650 (**S56L**); 8840 (**S88L**)
- CRI: ≥ 80
- CCT: Selectable 3000K/4000K/5000K
- Input Power: 20W (**S26L**); 22W/33W/45W (**S56L**); 33W/50W/69W (**S88L**)
- Dimmable: 0-10V to 10%
- Operating Temperature Range:
 - (2ft. & 4ft. w/out EB): -40°F to 113°F (-40°C to 45°C)
 - (4ft. w/EB): 32°F to 113°F (0°C to 45°C)
 - (8 ft. w/out EB): -40°F to 104°F (-40°C to 40°C)
 - (8 ft. w/EB): 32°F to 104°F (0°C to 40°C)
- Estimated L₇₀ Lifetime @ 25°C (77°F): >100,000 hours
- Limited Warranty: 5-Year*
- Replaces: 2 x F17T8 (**S26L**); 1 x F54T5HO (**S56L**); 2 x F54T5HO (**S88L**)

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none">• FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions• Field selectable color temp and light output• Integrated 90-minute emergency driver option available• Surge protection comes standard: 2kV (2-foot and 8-foot), 4kV (4-foot)	<ul style="list-style-type: none">• Industrial• Commercial• Offices• Retail• Residential• Manufacturing	<ul style="list-style-type: none">• Universal (120-277V Operation)

CERTIFICATIONS:

CA RESIDENTS WARNING: Cancer and Reproductive Harm – www.p65warnings.ca.gov



C-STRIP-B-SCCT SERIES

ORDERING INFORMATION


Example SKU: C-STRIP-B-LIN4-S56L-SCCT-UL-WH-EB

C-STRIP	B			SCCT	UL	WH	
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	SELECTABLE CCT'S	VOLTAGE	HOUSING COLOR	EMERGENCY BACKUP OPTION
C-STRIP	B	LIN2 2-foot	S26L 2630 Lumens (20W)*	SCCT 3000K, 4000K, 5000K	UL Universal 120-277V Operation	WH White	[blank] w/o Emergency backup option EB Emergency Battery Back Up - Provides 4W (4') or 8W (8') of power and 90 minutes of emergency operation - Available only with 4' and 8' luminaires
		LIN4 4-foot	S56L 2950 Lumens (22W)* 4420 Lumens (33W)* 5650 Lumens (45W)*				
		LIN8 8-foot	S88L 4520 Lumens (33W)* 6850 Lumens (50W)* 8840 Lumens (69W)*				


*Lumen values are measured at 4000K.

S26L

24-1/8" L
(610mm)




2-5/8" H
(51mm)




3" W
(76mm)

S56L

48" L
(1220mm)



2-5/8" H
(51mm)



3" W
(76mm)

S88L

96" L
(2439mm)



2-5/8" H
(51mm)



3" W
(76mm)

SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
(S26L): 24-1/8" L x 3" W x 2-5/8" H	2.05 lbs.	10-15 feet	End to end, or 1 to 1-1/2 times the mounting height
(S56L): 48" L x 3" W x 2-5/8" H	3.76 lbs., (w/o EB) 4.12 lbs. (w/EB)		
(S88L): 96" L x 3" W x 2-5/8" H	8.02 lbs., (w/o EB) 8.38 lbs. (w/EB)		

C-STRIP-B-SCCT SERIES

FIXTURE SPECIFICATIONS

HOUSING	High quality steel with white polyester powder coat finish. 3mil thickness for superior corrosion resistance and maximum environmental durability
LENS ASSEMBLY	Frosted polycarbonate diffuser lens for superior light uniformity and glare reduction
MOUNTING	Keyhole slots for surface mounting or suspended mounting using hook and chain (sold separately)

LUMINAIRE AND ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L ₇₀ LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
(2ft. & 4ft. w/out EB): -40°F to 113°F (-40°C to 45°C) (4ft. w/EB): 32°F to 113°F (0°C to 45°C) (8 ft. w/out EB): -40°F to 104°F (-40°C to 40°C) (8 ft. w/EB): 32°F to 104°F (0°C to 40°C)	>100,000 Hours	>.9 at full load	<20% at full load




SKU	REPLACES	LUMEN OUTPUT	SYSTEM WATTS	CURRENT DRAW (AMPS)			
				120V	208V	240V	277V
C-STRIP-B-LIN2-S26L-SCCT-UL-WH	2-Lamp F17T8	2630L	20W	0.160	0.092	0.080	0.069
C-STRIP-B-LIN4-S56L-SCCT-UL-WH	1-lamp T5H0	5650L/ 4420L/ 2950L	45W/33W/22W	0.351	0.202	0.175	0.152
C-STRIP-B-LIN4-S56L-SCCT-UL-WH-EB							
C-STRIP-B-LIN8-S88L-SCCT-UL-WH	2-lamp T5H0	8840L/ 6850L/ 4520L	69W/50W/33W	0.544	0.314	0.272	0.235
C-STRIP-B-LIN8-S88L-SCCT-UL-WH-EB							

WARRANTY AND CERTIFICATIONS

WARRANTY	cULus LISTED	DLC
5-Year-Limited*	Damp Locations	5.1 Standard

C-STRIP-B-SCCT SERIES

ACCESSORIES

	<p>MICROWAVE MOTION SENSOR 120-277V</p> <p>SKU: C-ACC-MW-L USE: Microwave motion sensor, recommended for 8'-20' mounting heights. Adjustable dip switches for time delays, and step dimming controls. 120-277V. For use with C-STRIP-B and C-WR-B Series.</p>
	<p>WIRE GUARD 2-FOOT</p> <p>SKU: C-STRIP-A-WG2 USE: White, powder-coated steel 2-foot wire guard provides added durability for more demanding applications. For use with C-STRIP-B Series.</p>
	<p>WIRE GUARD 4-FOOT</p> <p>SKU: C-STRIP-A-WG4 USE: White, powder-coated steel 4-foot wire guard provides added durability for more demanding applications. For use with C-STRIP-B Series. Note: When using with C-STRIP-B-LIN8 Series, (2) 4-foot wire guards are required.</p>