

PORTFOLIO AT A GLANCE

INDUSTRIAL / WAREHOUSE / MANUFACTURING

Better Light for Demanding Spaces.

HIGH-BAY LUMINAIRES



HXB SERIES

- 35,600 - 71,700 lumens
- Up to 150 LPW
- Input Power: 276W - 485W
- Operating temperature: -40°C to +60°C
- Input Voltage: 120-277V (UL), 347-480V (UH)
- IP6X optics



KBL SERIES

- 9,000 - 30,000 lumens
- Up to 156 LPW
- Input Power: 62W - 190W
- Operating temperature: -40°C up to 50°C
- Input Voltage: 120-277V (UL), 347-480V (UH)
- IP65 optical assembly
- Onboard emergency battery backup



C-LITE® PHB SERIES

- 12,500 - 39,000 lumens
- Up to 150 LPW
- Input Power: 90W - 275W
- Operating temperature: from -4°F to 104°F (-20°C to 40°C)
- Input Voltage: 120-277V (UL), 347-480V (UH)



C-LITE® RD SERIES

- 14,000 - 33,600 lumens
- Up to 140 LPW
- Input Power: 100W - 240W
- Operating temperature: from -4°F to 122°F (-20°C to 50°C)
- Input Voltage: 120-277V (UL), 347-480V (UH)

VAPOR TIGHT LUMINAIRES



WS SERIES

- 4,100 or 6,100 lumens
- Up to 142 LPW
- Input Power: 30W - 43W
- IP65 and IP66 rated for indoor and covered wet locations
- NSF Splash Zone II certified
- Diffused acrylic or polycarbonate lenses



C-LITE® VT LINEAR SERIES

- 5,000 - 7,800 lumens
- Up to 141 LPW
- Input Power: 36W - 56W
- Operating temperature: -40°F to 104°F (-40°C to 40°C)
- Input Voltage: 120V-277V (UL)

STRIP LUMINAIRES

LS SERIES

- 3,400 - 12,000 lumens
- Up to 135 LPW
- 31W - 92W
- Three optic lens options: Lambertian, Aisle Lighter, Asymmetric Wall Wash
- 4' and 8' sizes
- Available in round and square lenses

